

Engineered

Dual core



Engineered floor composed of a real sawn hardwood top layer on a vertical quartersawn softwood Wickham's most rigorous standards.



CONSTRUCTION:

100% North American Hardwood/Red Pine

FINISH:

Polyurethane—UV-cured: 5 degree, Matte 10, satin 35, semi-gloss 55

PRODUCT LENGTHS:

12 in. (305 mm) to 84 in. (2,134 mm)

AVERAGE LENGTH:

40 in. (1,016 mm) to 43 in. (1,092 mm)

THICKNESS:

3/4 in. (19 mm)

SPECIES:

Red Oak

GRADE:

Select

WIDTH:

5 in.

SQUARE FOOTAGE (PER BOX):

29 square feet

TOP LAYER:

5/32 in. (4mm) Sliced top layer

MATCH:

Tongue-and-groove

PROFILE:

4 sides micro-beveled

INSTALLATION:

Glued, nailed/stapled, floated

INSTALL APPLICATION:

On, above or below ground level

SUBFLOOR:

Wood, concrete, radiant heat*
(see manufacturer for approved system)

ACCESSORIES AVAILABLE:

Nosings, reducers, t-moldings,
stain can, touch up pen

SANDING:

Can be professionally sanded 3-4 times



FLOORS OF UNPARALLELED QUALITY.

1031, 7^e RANG, WICKHAM
QUEBEC, CANADA J0C 1S0

1888 4 WICKHAM
FOLLOW US ON FACEBOOK

wickhamhardwood.com

