

Engineered

# Flex core

Under humid conditions, an engineered floor offers greater stability than a regular hardwood floor. It's therefore an ideal option for condominiums and sub-levels work, because it can easily be installed on concrete surfaces. Made with a fileted wood block core, with a Basswood backing, and topped with our usual 4mm (5/32 in.) top layer of hardwood, this new engineered platform meets Wickham's most rigorous standard.



**CONSTRUCTION:**

100% North American Hardwood / Red Pine / Basswood

**FINISH:**

Polyurethane—UV-cured: 5 degree, Matte 10, satin 35, semi-gloss 55

**PRODUCT LENGTHS:**

12 in. (305 mm) to 84 in. (2,134 mm)

**AVERAGE LENGTH:**

40 in. (1,016 mm) to 43 in. (1,092 mm)

**THICKNESS:**

3/4 in. (19 mm)

**SPECIES:**

Red Oak, Hard Maple, White Oak

**GRADE:**

Select

**WIDTH:**

5 in. and 7 in.

**SQUARE FOOTAGE (PER BOX):**

5/8 in. (15 mm) x 5 in. – 29 square feet

3/4 in. (19 mm) x 5 in. – 23 square feet

3/4 in. (19 mm) x 7 in. – 16 square feet

**TOP LAYER:**

5/32 in. (4 mm) Sliced top layer

**MATCH:**

Tongue-and-groove

**PROFILE:**

4 sides micro-beveled

**INSTALLATION:**

Glued, nailed/stapled, floated

**INSTALL APPLICATION:**

On, above or below ground level

**SUBFLOOR:**

Wood, concrete, radiant heat\*  
(see manufacturer for approved system)

**ACCESSORIES AVAILABLE:**

Nosings, reducers, t-moldings,  
stain can, touch up pen

**SANDING:**

Can be professionally sanded 3-4 times



FLOORS OF UNPARALLELED QUALITY.

1031, 7<sup>e</sup> RANG, WICKHAM  
QUEBEC, CANADA J0C 1S0

1 888 4 WICKHAM  
FOLLOW US ON FACEBOOK

wickhamhardwood.com

