

Engineered

Baltic Birch

Under humid conditions, an engineered floor offers greater stability than regular hardwood floor. And because it can be easily installed on concrete surfaces. It's the ideal choice for condominiums and basements. Made with a core of Baltic Birch wood veneered with a 5/32 in. (4mm) layer of hardwood, this engineered floor meets Wickham's most rigorous standards.



CONSTRUCTION: 100% North American Hardwood/Baltic Birch

FINISH:

UV polyurethane finish, reinforced with aluminum oxide: 5 degree, Matte 10, satin 35, semi-gloss 55

PRODUCT LENGTHS:

14 in. (355.6 mm) to 84 in. (2,134 mm)

AVERAGE LENGTH:

40 in. (1,016 mm) to 43 in. (1,092 mm)

THICKNESS:

½ in. (12mm) and ¾ in (19mm)

SPECIES:

Red Oak, Ash, Hard Maple, White Oak

GRADE:

Select

WIDTH:

5 in. And 7 in.

SQUARE FOOTAGE (PER BOX):

29 sft - ½ x 5 ln.

23 sft - ¾ x 5 ln.

16 sft - ¾ x 7 ln.

TOP LAYER:

5/32 in. (4mm) Sliced top layer

MATCH:

Tongue-and-groove

PROFILE:

4 sides micro-beveled

INSTALLATION:

Glued, nailed/stapled, floated

INSTALL APPLICATION:

On, above or below ground level

SUBFLOOR:

Wood, concrete, radiant heat*
(see manufacturer for approved system)

ACCESSORIES AVAILABLE:

Nosings, reducers, t-moldings,
stain can, touch up pen

SANDING:

Can be professionally sanded 3-4 times



FLOORS OF UNPARALLELED QUALITY.

1031, 7^e RANG, WICKHAM
QUEBEC, CANADA J0C 1S0

wickhamhardwood.com

1 888 4 WICKHAM
FOLLOW US ON FACEBOOK

