



Application Instruction for Stain Cans



GENERAL

- Apply only on bare wood. Surfaces should be completely free from other finishes.
- For easy clean-up, use paint thinner.

APPLICATION

1. We recommend sanding the wood with 150-180 grit paper and clean the floor.
2. Stir well before and during use.
3. Spot test the stain on a hidden area of wood to confirm the desired color.
4. Apply with a brush or clean, lint-free cloth. Remove excess with a lint-free cloth.
5. After 1 hour, apply a second coat for a darker color.
6. Allow a minimum of 2 hours before applying a protective finish.

DANGER

- Fumes may be harmful. DANGER OF COMBUSTION.
- Do not swallow. Do not breathe vapors. Use only in a well-ventilated area.
- If adequate ventilation cannot be maintained, wear a vapor respirator.
- Avoid contact with skin and eyes. Wear rubber gloves and safety glasses when handling.
- Close container tightly after each use. KEEP OUT OF REACH OF CHILDREN.

IMPORTANT

- Do not use or store near heat, sparks, flames, or other sources of ignition.
- Materials such as rags used with this product may spontaneously combust if improperly disposed of or stored. After use, place rags and other materials in water or lay them flat to dry, then discard in accordance with local fire regulations.

FIRST AID TREATMENT

- Contains mineral spirits.
- If swallowed, call a Poison Control Center or a doctor immediately. Do not induce vomiting.
- If inhaled, move the person to fresh air.
- If in eyes, flush with water for at least 15 minutes.
- If on skin, clean thoroughly with soap and water. If irritation persists, consult a physician.

COVERAGE

- Covers approximately 100 sq. ft.

AVAILABILITY

- Available in certain colors only. Contact your store for more details.

Manufactured and printed in Canada



Superior Quality
Cutting-Edge Technology
Exceptional Durability



WICKHAMHARDWOOD.COM

FOLLOW US FACEBOOK AND INSTAGRAM

1031, 7^E RANG, WICKHAM
(QUÉBEC), CANADA J0C 1S0
1 888 4 WICKHAM

