

Euro Engineered

White Oak

Under humid conditions, an engineered floor offers greater stability than regular hardwood floor. It is the ideal choice for condominiums and basements because it can easily be installed on concrete surfaces. Made with a 3-ply core with a 5/32" (4mm) layer of hardwood, our Euro Engineered line offers the pristine look and stability of European White Oak whilst meeting Wickham's most rigorous standards.



CONSTRUCTION: 4mm European White Oak top layer on a 3-ply core with a 3mm Red Oak backing

FINISH:

Polyurethane–UV-cured: 5 degree, Matte 10, satin 35, semi-gloss 55

PRODUCT LENGTHS:

Random lengths 80% 70 inches or more.

AVERAGE LENGTH:

Approximately 70 inches or more.

THICKNESS:

¾ in (19mm)

SPECIES:

White Oak

GRADE:

Select (AB) and Cottage (ABCD)

WIDTH:

7 ½ in.

SQUARE FOOTAGE (PER BOX):

18 square feet

TOP LAYER: 5/32 in. (4mm) Sliced top layer

MATCH:

Tongue-and-groove

PROFILE:

4 sides micro-beveled

INSTALLATION:

Glued, nailed/stapled, floated

INSTALL APPLICATION:

On, above or below ground level

SUBFLOOR:

Wood, concrete, radiant heat*
(see manufacturer for approved system)

ACCESSORIES AVAILABLE:

Nosings, reducers, t-moldings, stain can, touch up pen

SANDING:

Can be professionally sanded 3-4 times



FLOORS OF UNPARALLELED QUALITY.

1031, 7^e RANG, WICKHAM
QUEBEC, CANADA J0C 1S0

wickhamhardwood.com

1 888 4 WICKHAM
FOLLOW US ON FACEBOOK

